

HYDRO - CYCLONE SAND WASHING PLANT




- HIGH PERFORMANCE DE-WATERING SCREEN EQUIPPED WITH LONG LIFE
 PU MESH & RELIABLE VIBRATORY MOTORS
- PROVEN CYCLONE DESIGN ASSURES FINE REMOVAL, PU LINED CYCLONE GIVES LONGER DURABILITY
- MULTI-FUNCTION SINGLE POINT WATER INLET PROVIDES EASE OF INSTALLATION AND MAINTENANCE
- SLURRY DISTRIBUTION AT OVERHEAD TANK FOR EASE OF MAINTENANCE OF DISCHARGE LINE



Comprehensive Quarry & Mining Solutions, Engineered to the Best

www.maxwellcrushtech.com





TECHNICAL DATA

Model Name	Dewatering Screen Size (Length mm x Width mm)	Dewatering Screen Power (KW / HP)	Slurry Pump Size Suction (inch) / Delivery (inch)	Slurry Pump Flow Rate (M3 / HR)	Slurry Pump Power (KW / HP)	Hydro Cyclone Size (mm)	Capacity (TPH)
HWP 80	2500 x 1500	(4.4 (2.2 x 2) / 6 (3 x 2)	4/3	125	15 / 20	400	70 - 80
HWP 120	3000 x 1800	(7.4 (3.7 x 2) 10 (5 x 2)	6/4	200	30 / 40	500	100 - 120
HWP 160	4000 x 1800	(14.2 (7.1 x 2) / 20 (10 x 2)	8/6	250	37 / 50	600	150 - 160

Note :-

- Capacity Is Based on 15% fines in Feed material Of Crush Sand. Capacity Varies Due To Feed Material Particle Size Gradation.
- The Detail Including Display, Construction, Technical Information, Etc. Are For Information Only And Subject To Change Without Prior Notice.
- Scope Of Supply May Differ From The Display Presented Here And It Is Fully As Per The Commercial Offer.

MAXWELL CRUSHTECH

- @ UNIT-1 : Block No. 188, Opp. Futura Engineering, Isand Road, At.: Chhatral, Tal.: Kalol, Dist.: Gandhinagar, Gujarat-382729, INDIA.
- 🙎 UNIT·2 : 26, At.: Bibipura, Opp. Giriraj Petrolium, Tal.: Bayad, Dist.: Aravalli, Gujarat·383325, INDIA.
- **℅ : +91-99251 25175, +91-99252 45504**
- 🖂 : maxwelldapatel@gmail.com , dapatel@maxwellcrushtech.com

Comprehensive Quarry & Mining Solutions, Engineered to the Best

www.maxwellcrushtech.com